

NATIONAL CHEMICAL LABORATORIES, INC.

SAFETY DATA SHEET

	Section 1 - Io	lentification	
Product Identifier	BIG PUNCH Instant Acting Oven & Grille Renov	vator	
Other means of identification	1104		
Recommended use	Cold Oven & Grille Renovator		
Recommended restrictions	For commercial and industrial use only.		
Manufacturer / Importer / Supp	lier / Distributor Information		
Company Name	National Chemical Laboratories of PA, Inc.		
Address	401 N. 10th Street - Philadelphia, PA 19123		
Telephone	1 (215) 922-1200		
Supplier Email	info@nclonline.com		
Contact	CHEM-TEL		
Emergency Phone	1 (800) 255-3924		
	Section 2 - Hazard	l(s) Identification	
SDS Hazards and	d Warnings are based on the undiluted product.	Refer to diluted SDS for Ready-To-Use Hazards a	nd Warnings.
	Classification	Category	
Physical Hazards	Not Classified		
Health Hazards	Serious eye damage/eye irritation	1	
	Skin corrosion/irritation	1	
OSHA defined hazards	Not Classified.		
abel Elements			
Hazard Symbol	$\mathbf{\wedge}$		
Signal Word	Danger		
Hazard Statement	Causes severe skin burns and eye damage.		
Precautionary statement			
Prevention	Do not breathe spray or mist. Wash thorough protection/face protection.	y after handling. Wear protective gloves/protective	e clothing/eye
Response	skin with water/shower. If inhaled: Remove per cautiously with water for several minutes. Rer	miting. If on skin (or hair): Take off immediately all erson to fresh air and keep comfortable for breathi nove contact lenses, if present and easy to do. Con t (see this label). Wash contaminated clothing befo	ng. If in eyes: Rinse tinue rinsing. Immediately
Storage	Store locked up.		
Disposal	Dispose of contents/container in accordance v	vith local/regional/national/international regulatio	ns.
Hazard(s) not otherwise classified (HNOC)	None known.		
	Section 3 - Composition/Ir	formation on ingredients	
Mixture			
Hazardous Components	Ingredient Name	CAS #	%
	Sodium Hydroxide	1310-73-2	10 - 20
	Disodium metasilicate	6834-92-0	1 - 5
	Section 4 - Firs	t-aid Measures	
nhalation	If breathing is difficult, remove to fresh air and symptoms develop or persist.	I keep at rest in a position comfortable for breathin	g. Call a physician if
Skin contact		g. Rinse skin with water/shower. Call a physician or by a physician. Wash contaminated clothing before	
Eye contact	Immediately flush eyes with plenty of water for Continue rinsing. Call a physician or poison co	or at least 15 minutes. Remove contact lenses, if pro ntrol center immediately.	esent and easy to do.
Ingestion	Call a physician or poison control center imme so that stomach content doesn't get into the l	diately. Rinse mouth. Do not induce vomiting. If vo ungs.	miting occurs, keep head low

Most Important symptoms						
/effects, acute and delayed Indication of immediate medical attention and special treatment	swelling, and blurred vision. Permane Provide general supportive measures	ent eye dam and treat s	age including blind ymptomatically. Ch	damage. Symptoms may include stinging, tearing, redness, ness could result. emical burns: Flush with water immediately. While an ambulance. Continue flushing during transport to		
	hospital. Keep victim under observation. Symptoms may be delayed Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.					
General Information	Ensure that medical personnel are aw	vare of the	material(s) involved	, and take precautions to protect themselves.		
	Section 5 - F	ire-figl	nting measu	res		
Suitable extinguishing media	Water fog. Foam. Dry chemical powd	er. Carbon	dioxide (CO2).			
Unsuitable extinguishing media	Do not use water jet as an extinguish	er, as this w	ill spread the fire.			
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.					
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.					
Fire-fighting equipment /instructions	Move containers from fire area if you	ı can do it w	ithout risk.			
General fire hazards	No unusual fire or explosion hazards	noted.				
Specific Methods	Use standard firefighting procedures	and conside	er the hazards of otl	ner involved materials.		
	Section 6 - Acc	idental	release me	asures		
Personal precautions, protective equipment and emergency procedures. Methods and materials for containment and cleaning up	appropriate protective equipment an containers or spilled material unless v should be advised if significant spillag Large Spills: Stop the flow of material plastic sheet to prevent spreading. At waterways, sewer, basements or con	d clothing c wearing app ges cannot b l, if this is w osorb in ver fined areas material (e.	luring clean-up. Do propriate protective the contained. For pe- thout risk. Dike the miculite, dry sand o Following product g. cloth, fleece). Cle	an surface thoroughly to remove residual		
Environmental precautions	Avoid discharge into drains, water co		-	sal, see section 15 of the 5D5.		
•	-		-			
	Section 7 -	Handliı	ng and stora			
			-	-		
Precautions for safe handling	ventilation. Wear appropriate person handling/storage.	get in eyes, al protectiv	on skin, or on cloth e equipment. Obse	ing. Avoid prolonged exposure. Provide adequate rve good industrial hygiene practices. Use care in		
Precautions for safe handling Conditions for safe storage, including any incompatibilities	ventilation. Wear appropriate person handling/storage.	get in eyes, al protectiv	on skin, or on cloth e equipment. Obse	ing. Avoid prolonged exposure. Provide adequate		
Conditions for safe storage,	ventilation. Wear appropriate person handling/storage.	get in eyes, al protectiv tly closed co	on skin, or on cloth e equipment. Obse ontainer. Store awa	ing. Avoid prolonged exposure. Provide adequate rve good industrial hygiene practices. Use care in y from incompatible materials (see Section 10 of the		
Conditions for safe storage, including any incompatibilities Occupational exposure limits	ventilation. Wear appropriate person handling/storage. Store locked up. Store in original tight Section 8 - Exposur	get in eyes, ial protectiv tly closed co re conti	on skin, or on cloth e equipment. Obse ontainer. Store awa	ing. Avoid prolonged exposure. Provide adequate rve good industrial hygiene practices. Use care in y from incompatible materials (see Section 10 of the		
Conditions for safe storage, including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for	ventilation. Wear appropriate person handling/storage. Store locked up. Store in original tight	get in eyes, ial protectiv tly closed co e conti	on skin, or on cloth e equipment. Obser ontainer. Store awar rol/personal	ing. Avoid prolonged exposure. Provide adequate rve good industrial hygiene practices. Use care in y from incompatible materials (see Section 10 of the protection		
Conditions for safe storage, including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Components	ventilation. Wear appropriate person handling/storage. Store locked up. Store in original tight Section 8 - Exposur Air Contaminants (29 CFR 1910.1000)	get in eyes, ial protectiv tly closed co 'e conti Type	on skin, or on cloth e equipment. Obser ontainer. Store awar rol/personal Value	ing. Avoid prolonged exposure. Provide adequate rve good industrial hygiene practices. Use care in y from incompatible materials (see Section 10 of the		
Conditions for safe storage, including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Components Sodium Hydroxide (CAS 131	ventilation. Wear appropriate person handling/storage. Store locked up. Store in original tight Section 8 - Exposur Air Contaminants (29 CFR 1910.1000) .0-73-2)	get in eyes, ial protectiv tly closed co e conti	on skin, or on cloth e equipment. Obser ontainer. Store awar rol/personal	ing. Avoid prolonged exposure. Provide adequate rve good industrial hygiene practices. Use care in y from incompatible materials (see Section 10 of the protection		
Conditions for safe storage, including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Components Sodium Hydroxide (CAS 131 US. ACGIH Threshold Limit Va	ventilation. Wear appropriate person handling/storage. Store locked up. Store in original tight Section 8 - Exposur Air Contaminants (29 CFR 1910.1000) .0-73-2)	get in eyes, ial protectiv tly closed co r e cont i Type TWA	on skin, or on cloth e equipment. Obser ontainer. Store awa rol/personal Value 2 mg/m ³	ing. Avoid prolonged exposure. Provide adequate rve good industrial hygiene practices. Use care in y from incompatible materials (see Section 10 of the protection Form		
Conditions for safe storage, including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Components Sodium Hydroxide (CAS 131 US. ACGIH Threshold Limit Va Component	ventilation. Wear appropriate person handling/storage. Store locked up. Store in original tight Section 8 - Exposur Air Contaminants (29 CFR 1910.1000) .0-73-2) alues	get in eyes, ial protectiv tly closed co re contr Type TWA Type	on skin, or on cloth e equipment. Obser ontainer. Store awa rol/personal Value 2 mg/m ³ Value	ing. Avoid prolonged exposure. Provide adequate rve good industrial hygiene practices. Use care in y from incompatible materials (see Section 10 of the protection		
Conditions for safe storage, including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Components Sodium Hydroxide (CAS 131 US. ACGIH Threshold Limit Va Component Sodium Hydroxide (CAS 131	ventilation. Wear appropriate person handling/storage. Store locked up. Store in original tight Section 8 - Exposur Air Contaminants (29 CFR 1910.1000) .0-73-2) alues .0-73-2)	get in eyes, ial protectiv tly closed co r e cont i Type TWA	on skin, or on cloth e equipment. Obser ontainer. Store awa rol/personal Value 2 mg/m ³	ing. Avoid prolonged exposure. Provide adequate rve good industrial hygiene practices. Use care in y from incompatible materials (see Section 10 of the protection Form		
Conditions for safe storage, including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Components Sodium Hydroxide (CAS 131 US. ACGIH Threshold Limit Va Component Sodium Hydroxide (CAS 131 US. NIOSH: Pocket Guide to Cl	ventilation. Wear appropriate person handling/storage. Store locked up. Store in original tight Section 8 - Exposur Air Contaminants (29 CFR 1910.1000) .0-73-2) alues .0-73-2)	get in eyes, al protectiv tly closed co re conti Type TWA Type Ceiling	on skin, or on cloth e equipment. Obser- ontainer. Store awar rol/personal Value 2 mg/m ³ Value 2 mg/m ³	ing. Avoid prolonged exposure. Provide adequate rve good industrial hygiene practices. Use care in y from incompatible materials (see Section 10 of the protection Form		
Conditions for safe storage, including any incompatibilities Dccupational exposure limits US. OSHA Table Z-1 Limits for Components Sodium Hydroxide (CAS 131 US. ACGIH Threshold Limit Va Component Sodium Hydroxide (CAS 131 US. NIOSH: Pocket Guide to Cl Components	ventilation. Wear appropriate person handling/storage. Store locked up. Store in original tight Section 8 - Exposur Air Contaminants (29 CFR 1910.1000) .0-73-2) alues .0-73-2) hemical Hazards	get in eyes, al protectiv tly closed co re conti Type TWA Type Ceiling Type	on skin, or on cloth e equipment. Obser ontainer. Store awar rol/personal Value 2 mg/m ³ Value 2 mg/m ³	ing. Avoid prolonged exposure. Provide adequate rve good industrial hygiene practices. Use care in y from incompatible materials (see Section 10 of the protection Form		
Conditions for safe storage, ncluding any incompatibilities Dccupational exposure limits US. OSHA Table Z-1 Limits for Components Sodium Hydroxide (CAS 131 US. ACGIH Threshold Limit Va Component Sodium Hydroxide (CAS 131 US. NIOSH: Pocket Guide to CI Components Sodium Hydroxide (CAS 131	ventilation. Wear appropriate person handling/storage. Store locked up. Store in original tight Section 8 - Exposur Air Contaminants (29 CFR 1910.1000) .0-73-2) alues .0-73-2) hemical Hazards	get in eyes, al protectiv tly closed co 'e conti Type TWA Type Ceiling Type Ceiling	on skin, or on cloth e equipment. Obser- ontainer. Store awar rol/personal Value 2 mg/m ³ Value 2 mg/m ³ Value 2 mg/m ³	ing. Avoid prolonged exposure. Provide adequate rve good industrial hygiene practices. Use care in y from incompatible materials (see Section 10 of the protection Form		
Conditions for safe storage, including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Components Sodium Hydroxide (CAS 131 US. ACGIH Threshold Limit Va Component Sodium Hydroxide (CAS 131 US. NIOSH: Pocket Guide to Cl Components Sodium Hydroxide (CAS 131 Biological limit values	ventilation. Wear appropriate person handling/storage. Store locked up. Store in original tight Section 8 - Exposur Air Contaminants (29 CFR 1910.1000) .0-73-2) alues .0-73-2) hemical Hazards .0-73-2) No biological exposure limits noted for	get in eyes, al protectiv tly closed co re conti Type TWA Type Ceiling Type Ceiling or the ingre	on skin, or on cloth e equipment. Obser- ontainer. Store awar rol/personal Value 2 mg/m ³ Value 2 mg/m ³ Value 2 mg/m ³ dient(s).	ing. Avoid prolonged exposure. Provide adequate rve good industrial hygiene practices. Use care in y from incompatible materials (see Section 10 of the protection Form Form		
Conditions for safe storage, including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Components Sodium Hydroxide (CAS 131 US. ACGIH Threshold Limit Va Component Sodium Hydroxide (CAS 131 US. NIOSH: Pocket Guide to CI Components Sodium Hydroxide (CAS 131 Biological limit values Appropriate engineering	ventilation. Wear appropriate person handling/storage. Store locked up. Store in original tight Section 8 - Exposur Air Contaminants (29 CFR 1910.1000) 0-73-2) hemical Hazards .0-73-2) hemical Hazards .0-73-2) No biological exposure limits noted for Good general ventilation (typically 10 conditions. If applicable, use process airborne levels below recommended	get in eyes, lal protectiv tly closed co re conti Type TWA Type Ceiling Type Ceiling or the ingre D air change enclosures, exposure li	on skin, or on cloth e equipment. Obser- ontainer. Store awar rol/personal Value 2 mg/m ³ Value 2 mg/m ³ Value 2 mg/m ³ dient(s). s per hour) should b local exhaust ventii mits. If exposure lim	ing. Avoid prolonged exposure. Provide adequate rve good industrial hygiene practices. Use care in y from incompatible materials (see Section 10 of the protection Form		
Conditions for safe storage, including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Components Sodium Hydroxide (CAS 131 US. ACGIH Threshold Limit Va Component Sodium Hydroxide (CAS 131 US. NIOSH: Pocket Guide to Cl Components Sodium Hydroxide (CAS 131 Biological limit values Appropriate engineering controls	ventilation. Wear appropriate person handling/storage. Store locked up. Store in original tight Section 8 - Exposur Air Contaminants (29 CFR 1910.1000) 0-73-2) hemical Hazards .0-73-2) hemical Hazards .0-73-2) No biological exposure limits noted for Good general ventilation (typically 10 conditions. If applicable, use process airborne levels below recommended	get in eyes, al protectiv tly closed co re conti Type TWA Type Ceiling or the ingre o air change enclosures, exposure li th facilities a	on skin, or on cloth e equipment. Obser- ontainer. Store awar rol/personal Value 2 mg/m ³ Value 2 mg/m ³ Value 2 mg/m ³ dient(s). s per hour) should b local exhaust ventii mits. If exposure lim	rve good industrial hygiene practices. Use care in y from incompatible materials (see Section 10 of the protection Form Form we used. Ventilation rates should be matched to lation, or other engineering controls to maintain hits have not been established, maintain airborne		
Conditions for safe storage, including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Components Sodium Hydroxide (CAS 131 US. ACGIH Threshold Limit Va Component Sodium Hydroxide (CAS 131 US. NIOSH: Pocket Guide to Cl Components Sodium Hydroxide (CAS 131 Biological limit values Appropriate engineering controls	ventilation. Wear appropriate person handling/storage. Store locked up. Store in original tight Section 8 - Exposur Air Contaminants (29 CFR 1910.1000) .0-73-2) alues .0-73-2) hemical Hazards .0-73-2) No biological exposure limits noted for Good general ventilation (typically 10 conditions. If applicable, use process airborne levels below recommended levels to an acceptable level. Eye was	get in eyes, al protectiv tly closed co e conti Type TWA Type Ceiling Type Ceiling or the ingre enclosures, exposure li th facilities a	on skin, or on cloth e equipment. Obser- ontainer. Store awar rol/personal Value 2 mg/m ³ Value 2 mg/m ³ Value 2 mg/m ³ dient(s). s per hour) should b local exhaust venti mits. If exposure lin and emergency show	ing. Avoid prolonged exposure. Provide adequate rve good industrial hygiene practices. Use care in y from incompatible materials (see Section 10 of the protection Form Form be used. Ventilation rates should be matched to lation, or other engineering controls to maintain hits have not been established, maintain airborne wer must be available when handling this product.		
Conditions for safe storage, including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Components Sodium Hydroxide (CAS 131 US. ACGIH Threshold Limit Va Component Sodium Hydroxide (CAS 131 US. NIOSH: Pocket Guide to Cl Components Sodium Hydroxide (CAS 131 Biological limit values Appropriate engineering controls	ventilation. Wear appropriate person handling/storage. Store locked up. Store in original tight Section 8 - Exposur Air Contaminants (29 CFR 1910.1000) .0-73-2) alues .0-73-2) hemical Hazards .0-73-2) No biological exposure limits noted for Good general ventilation (typically 10 conditions. If applicable, use process airborne levels below recommended levels to an acceptable level. Eye was uch as personal protective equipment	get in eyes, al protectiv tly closed co e conti Type TWA Type Ceiling Type Ceiling or the ingre 0 air change enclosures, exposure li th facilities a	on skin, or on cloth e equipment. Obser- ontainer. Store awar rol/personal Value 2 mg/m ³ Value 2 mg/m ³ Value 2 mg/m ³ dient(s). s per hour) should b local exhaust ventii mits. If exposure lim and emergency show safety glasses with	ing. Avoid prolonged exposure. Provide adequate rve good industrial hygiene practices. Use care in y from incompatible materials (see Section 10 of the protection Form Form be used. Ventilation rates should be matched to lation, or other engineering controls to maintain hits have not been established, maintain airborne wer must be available when handling this product.		
Conditions for safe storage, including any incompatibilities Occupational exposure limits US. OSHA Table Z-1 Limits for Components Sodium Hydroxide (CAS 131 US. ACGIH Threshold Limit Va Component Sodium Hydroxide (CAS 131 US. NIOSH: Pocket Guide to Cl Components Sodium Hydroxide (CAS 131 Biological limit values Appropriate engineering controls Individual protection measures, su Eye/face protection Skin protection	ventilation. Wear appropriate person handling/storage. Store locked up. Store in original tight Section 8 - Exposur Air Contaminants (29 CFR 1910.1000) (0-73-2) hues (0-73-2) hemical Hazards (0-73-2) No biological exposure limits noted for Good general ventilation (typically 10 conditions. If applicable, use process airborne levels below recommended levels to an acceptable level. Eye was uch as personal protective equipment If use of product risks exposure to con	get in eyes, al protectiv tly closed co e conti Type TWA Type Ceiling Type Ceiling or the ingre 0 air change enclosures, exposure li th facilities a ntact, wear	on skin, or on cloth e equipment. Obser- ontainer. Store awar rol/personal Value 2 mg/m ³ Value 2 mg/m ³ Value 2 mg/m ³ dient(s). s per hour) should b local exhaust venti mits. If exposure lim mits. If exposure lim safety glasses with ged use.	ing. Avoid prolonged exposure. Provide adequate rive good industrial hygiene practices. Use care in y from incompatible materials (see Section 10 of the protection Form Form be used. Ventilation rates should be matched to lation, or other engineering controls to maintain nits have not been established, maintain airborne wer must be available when handling this product. side shields.		

Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Section 9 - Physical and chemical properties

Appearance	Clear.
Physical state	Liquid.
Form	Thin clear liquid.
Color	Yellow.
Odor	Odorless.
Odor threshold	Not available.
рН	13.6
Melting point/freezing point	Not available.
Initial boinging point and	212 °F (100 °C)
boiling range	
Flash point	> 212.0 °F (> 100.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or expl	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Similar to water.
Vapor density	Similar to water.
Relative density	1.16 ± 0.01
Relative density temperature	75 °F (23.9 °C)
Solubilities (water)	Not available.
Partition Coefficient n-	Not available
octanol/water	
Auto-ignition temperature	Not Available
Decomposition temperature	Not Available
Viscosity	< 10 cP
Viscosity Temperature	75 °F (23.9 °C)

Section 10 - Stability and reactivity

Reactivity	Reacts violently with strong acids. This product may react with oxidizing agents.
Chemical stability	Material is stable under normal conditions.
Possiblity of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to Avoid	Do not mix with other chemicals. Contact with incompatible materials.
Incompatible materials	Acids. Oxidizing agents.
Hazardous Decomposition	No hazardous decomposition products are known.
Products	

Section 11 - Toxicological information

Information on likely routes of exposure

Ingestion	Causes digestive tract burns.
Inhalation	May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
Skin contact	Causes severe skin burns.
Eye contact	Causes serious eye damage.
Symptoms related to the physical, chemical and toxicological characteristics	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Information on toxicological effects.

Acute toxicity	Not expected to be	e acutely toxic.				
Components		Level	Туре	Code	Species	Results
Disodium metasilicate (CAS	6834-92-0)	Acute	Dermal	LD50	Rat	>5000 mg/kg, 24 hours
		Acute	Inhalation	LC50	Rat	> 2.06 mg/l, 4 hours
		Acute	Oral	LD50	Mouse	661.5 - 896.3 mg/kg
		Acute	Oral	LD50	Rat	994.7 - 1335.9 mg/kg

0.	AFEIT DAIA					
)-73-2)	Acute Oral	LD50	Rabbit	500 mg/kg		
Causes severe skin burns	and eye damage.					
Causes serious eye damag	ge.					
This product is not expect	ed to cause respiratory sens	sitization.				
This product is not expect	ed to cause skin sensitizatio	n.				
No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.						
This product is not consid	ered to be a carcinogen by I	ARC, ACGIH, NTP, or	OSHA.			
	ed to cause reproductive or	developmental effe	cts.			
Not classified.						
Not classified.						
Prolonged inhalation may	be harmful.					
	-					
				the possibility that large or		
No data available.						
No data available.						
No other adverse environ	mental effects (e.g. ozone d	epletion, photochen	nical ozone creatio	n potential, endocrine		
disruption, global warmin	g potential) are expected fro	om this component.				
Sectio	n 13 - Disposal c	onsideration	IS			
Dispose in accordance wit	th applicable federal, state, a	and local regulations	i.			
Dispose of in accordance	with local regulations.					
	Waste codes should be assigned by the user based on the application for which the product was used.					
			which the product	was used.		
	signed by the user based or th all applicable regulations.		which the product	was used.		
Dispose in accordance wit						
Dispose in accordance wit Since emptied containers	th all applicable regulations.	, follow label warnin	gs even after conta			
Dispose in accordance wit Since emptied containers	th all applicable regulations. may retain product residue,	, follow label warnin	gs even after conta			
Dispose in accordance wit Since emptied containers	th all applicable regulations. may retain product residue,	, follow label warnin	gs even after conta			
Dispose in accordance with Since emptied containers Section UN1824 SODIUM HYDROXIDE SOLU	th all applicable regulations. may retain product residue, on 14 - Transport	, follow label warnin	gs even after conta			
Dispose in accordance with Since emptied containers Section UN1824 SODIUM HYDROXIDE SOLU 8	th all applicable regulations. may retain product residue, on 14 - Transport	, follow label warnin	gs even after conta			
Dispose in accordance with Since emptied containers Section UN1824 SODIUM HYDROXIDE SOLU 8 II	th all applicable regulations. may retain product residue, on 14 - Transport JTION	follow label warnin	gs even after conta			
Dispose in accordance with Since emptied containers Section UN1824 SODIUM HYDROXIDE SOLU 8 II Read safety instructions, SI	th all applicable regulations. may retain product residue, on 14 - Transport	follow label warnin	gs even after conta			
Dispose in accordance with Since emptied containers Section UN1824 SODIUM HYDROXIDE SOLU 8 II Read safety instructions, SI B2, IB2, N34, T7, TP2	th all applicable regulations. may retain product residue, on 14 - Transport JTION	follow label warnin	gs even after conta			
Dispose in accordance with Since emptied containers Section UN1824 SODIUM HYDROXIDE SOLU 8 II Read safety instructions, SI B2, IB2, N34, T7, TP2 154	th all applicable regulations. may retain product residue, on 14 - Transport JTION	follow label warnin	gs even after conta			
Dispose in accordance with Since emptied containers Section UN1824 SODIUM HYDROXIDE SOLU 8 II Read safety instructions, SI B2, IB2, N34, T7, TP2 154 202	th all applicable regulations. may retain product residue, on 14 - Transport JTION	follow label warnin	gs even after conta			
Dispose in accordance with Since emptied containers Section UN1824 SODIUM HYDROXIDE SOLU 8 II Read safety instructions, SI B2, IB2, N34, T7, TP2 154	th all applicable regulations. may retain product residue, on 14 - Transport JTION	follow label warnin	gs even after conta			
Dispose in accordance with Since emptied containers Section UN1824 SODIUM HYDROXIDE SOLU 8 II Read safety instructions, SI B2, IB2, N34, T7, TP2 154 202	th all applicable regulations. may retain product residue, on 14 - Transport JTION	follow label warnin	gs even after conta			
Dispose in accordance with Since emptied containers Section UN1824 SODIUM HYDROXIDE SOLU 8 II Read safety instructions, SI B2, IB2, N34, T7, TP2 154 202 242	th all applicable regulations. may retain product residue, on 14 - Transport JTION DS and emergency procedur	follow label warnin	gs even after conta			
Dispose in accordance with Since emptied containers Societary SODIUM HYDROXIDE SOLU 8 II Read safety instructions, SI B2, IB2, N34, T7, TP2 154 202 242 UN1824	th all applicable regulations. may retain product residue, on 14 - Transport JTION DS and emergency procedur	follow label warnin	gs even after conta			
Dispose in accordance with Since emptied containers Societation So	th all applicable regulations. may retain product residue, on 14 - Transport JTION DS and emergency procedur	follow label warnin	gs even after conta			
Dispose in accordance with Since emptied containers Section UN1824 SODIUM HYDROXIDE SOLU 8 II Read safety instructions, SI B2, IB2, N34, T7, TP2 154 202 242 UN1824 SODIUM HYDROXIDE SOLU 8 II No.	th all applicable regulations. may retain product residue, on 14 - Transport JTION DS and emergency procedur	follow label warnin	gs even after conta			
Dispose in accordance with Since emptied containers Section UN1824 SODIUM HYDROXIDE SOLU 8 II Read safety instructions, SI B2, IB2, N34, T7, TP2 154 202 242 UN1824 SODIUM HYDROXIDE SOLU 8 II NO. 8L	th all applicable regulations. may retain product residue, on 14 - Transport JTION DS and emergency procedur	, follow label warnin information res before handling.	gs even after conta			
Dispose in accordance with Since emptied containers Section UN1824 SODIUM HYDROXIDE SOLU 8 II Read safety instructions, SI B2, IB2, N34, T7, TP2 154 202 242 UN1824 SODIUM HYDROXIDE SOLU 8 II NO. 8L	th all applicable regulations. may retain product residue, on 14 - Transport JTION DS and emergency procedur	, follow label warnin information res before handling.	gs even after conta			
Dispose in accordance with Since emptied containers Section UN1824 SODIUM HYDROXIDE SOLU 8 II Read safety instructions, SI B2, IB2, N34, T7, TP2 154 202 242 UN1824 SODIUM HYDROXIDE SOLU 8 II No. 8L Read safety instructions, SI	th all applicable regulations. may retain product residue, on 14 - Transport JTION DS and emergency procedur	, follow label warnin information res before handling.	gs even after conta			
Dispose in accordance with Since emptied containers Section UN1824 SODIUM HYDROXIDE SOLU 8 II Read safety instructions, SI B2, IB2, N34, T7, TP2 154 202 242 UN1824 SODIUM HYDROXIDE SOLU 8 II No. 8L Read safety instructions, SI UN1824	th all applicable regulations. may retain product residue, on 14 - Transport JTION DS and emergency procedur	, follow label warnin information res before handling.	gs even after conta			
Dispose in accordance with Since emptied containers Section UN1824 SODIUM HYDROXIDE SOLU 8 II Read safety instructions, SI B2, IB2, N34, T7, TP2 154 202 242 UN1824 SODIUM HYDROXIDE SOLU 8 II No. 8L Read safety instructions, SI	th all applicable regulations. may retain product residue, on 14 - Transport JTION DS and emergency procedur	, follow label warnin information res before handling.	gs even after conta			
	Causes serious eye damage This product is not expect This product is not expect No data available to indic This product is not consid This product is not expect Not classified. Not classified. Prolonged inhalation may Sectio The product is not classifi frequent spills can have a No data is available on the No data available. No data available. No other adverse environ disruption, global warmin	Causes severe skin burns and eye damage. Causes serious eye damage. This product is not expected to cause respiratory sens This product is not expected to cause skin sensitizatio No data available to indicate product or any component This product is not considered to be a carcinogen by I This product is not expected to cause reproductive or Not classified. Not classified. Not classified. Prolonged inhalation may be harmful. Section 12 - Ecologica The product is not classified as environmentally hazar frequent spills can have a harmful or damaging effect No data is available on the degradability of this produc No data available. No data available. No data available. No data available. No data available. No other adverse environmental effects (e.g. ozone d disruption, global warming potential) are expected from Section 13 - Disposal c	Causes severe skin burns and eye damage. Causes serious eye damage. This product is not expected to cause respiratory sensitization. This product is not expected to cause skin sensitization. No data available to indicate product or any components present at great This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or This product is not expected to cause reproductive or developmental effe Not classified. Not classified. Not classified. Prolonged inhalation may be harmful. Section 12 - Ecological Information No data is available on the degradability of this product. No data available. No data available. No data available. No data available. No data available. No other adverse environmental effects (e.g. ozone depletion, photochem disruption, global warming potential) are expected from this component. Section 13 - Disposal consideration	Causes severe skin burns and eye damage. Causes serious eye damage. This product is not expected to cause respiratory sensitization. This product is not expected to cause skin sensitization. No data available to indicate product or any components present at greater than 0.1% are n This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. This product is not expected to cause reproductive or developmental effects. Not classified. Not classified. Not classified. Prolonged inhalation may be harmful. Section 12 - Ecological Information The product is not classified as environmentally hazardous. However, this does not exclude a frequent spills can have a harmful or damaging effect on the environment. No data available. No data available. No data available. No data available. No data available. No data available. No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation disruption, global warming potential) are expected from this component.		

	•				
Environmental hazards Marine pollutant	No.				
EmS	F-A, S-B				
Special precautions for use		S and emergency procedures before handling			
Transportation in bulk	Read safety instructions, SDS and emergency procedures before handling. This substance/mixture is not intended to be transported in bulk.				
according to Annex II of MARPOL 73/78 and IBC Code					
	Sectio	n 15 - Regulatory Information			
US federal regulations		us Chemical" as defined by the OSHA Hazard Communication Stan U.S. EPA TSCA Inventory List.	idard, 29 CFR 1910.1200.		
US. OSHA Specifically Reg	t Notification (40 CFR707, Subpt gulated Substances (29 CFR 1910				
CERCLA Hazardous Subst	ance List (40 CFR 302.4				
Components		Result			
Sodium Hydro:	xide (CAS 1310-73-2)	LISTED			
Superfund Amendments	and Reauthorization Act of 1986	i (SARA)			
Hazard Categories	Immediate Hazard Yes				
	Delayed Hazard No				
	Fire Hazard No				
	Pressure Hazard No				
	Reactivity Hazard No				
SARA 302 Extremely haza		d.			
SARA 311/312 Hazardous					
SARA 313 (TRI reporting)	Not regu	lated.			
Other federal regulations					
	on 112 Hazardous Air Pollutants				
	on 112(r) Accidental Release Prev	vention (40 CFR 68.130) Not regulated.			
Safe Drinking Water Act (· · ·				
Food and Drug Administr	ation (FDA) Not regulated.				
US state regulations	Culoten en Lint	Commente			
US.Massachusetts RTK - S	Substance List	Components			
	ad Cara and its Dialet to Karaw A	Sodium Hydroxide (CAS 1310-73-2)			
US.New Jersey Worker a	nd Community Right-to-Know Ac	-			
		Sodium Hydroxide (CAS 1310-73-2)			
US.Pennsylvania RTK - Ha	izardous Substances	Components			
US.Rhode Island RTK		Sodium Hydroxide (CAS 1310-73-2)			
US.Rhode Island RTK		Components			
		Sodium Hydroxide (CAS 1310-73-2)	f 1096 (Dropposition CE), This		
		California Safe Drinking Water and Toxic Enforcement Act o material is not known to expose you to any chemicals curre reproductive toxins.			
International Inventories					
Country(s) or region	Inventory Name		On Inventory (yes/no)*		
Australia	Australian Invento	ory of Chemical Substances (AICS)	Yes		
Canada	Domestic Substan	ces List (DSL)	Yes		
Canada	Non-Domestic Sub	ostances List (NDSL)	No		
China		ing Chemical Substances in China (IECSC)	Yes		
Europe	European Invento	ry of Existing Commercial Chemical Substances (EINECS)	No		
Europe	European List of N	lotifed Chemical Substances (ELINCS)	No		

 New Zealand
 New Zealand Inventory
 Yes

 Philippines
 Philippine Inventory of Chemicals and Chemical Substances
 Yes

 Unites States Puerto Rico
 Toxic Substances Control Act (TSCA) Inventory
 Yes

 *A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).
 Yes

 *A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

 Section 16 - Other information, including date of preparation or last version

Existing Chemicals List (ECL)

Inventory of Existing and New Chemical Substances (ENCS)

Japan

Korea

Revision date	1/17/2021		
Version #	02		
HMIS Hazard Codes		PPE	A

No

Yes

Disclaimer

SAFETY DATA SHEET

The information contained herein was obtained from current and reliable sources. However, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions for use, handling, storage and disposal of this product are beyond the manufacturer's control, it is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense arising from the product's improper use. No warranty, expressed or implied, regarding the product described herein shall be created by or inferred from any statement or omission in this SDS. Various government agencies may have specific regulations concerning the transportation, handling, storage, use or disposal of this product which may not be reflected in this SDS. The user should review these regulations to ensure full compliance.